

# Logitank Klassic - LTKL 100

A self bunded and transportable KLASSIC tank for the safe storage and handling of diesel, petrol and oils. Ideal for refuelling vehicles, machinery, equipment and fleet.



Suitable for bulk fuel farm applications



Pictured with optional dispensing kit and lighting

## Specifications

| Description          |                       |
|----------------------|-----------------------|
| Safe Fill, litres    | 93,583 (95%)          |
| Length, mm           | 14,630                |
| Width, mm            | 2,438                 |
| Height, mm           | 3,200                 |
| Total Mass Empty, kg | 18,600                |
| Vent Pipe            | Standard              |
| Fluid Level Dipstick | Standard              |
| Compliance           | AS1940, AS1692, UL142 |

### Self bunded double wall design

- Fluid level dipstick for tank and interstitial space
- Vent pipe for tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Warranty – 5 years structural, 1 year on valves; conditions apply

### Options include:

- Inspection ladder
- Clip-on pump bay
- Dispensing and fuel management

*Disclaimer: Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras.*