

# Logitank Classic - LTKL 110

A self bunded and transportable KLASSIC tank for the safe storage and handling of diesel, petrol and oils. Ideal for refuelling vehicles, machinery, equipment and fleet.



Suitable for bulk fuel farm applications



Bulk lubricant farm with optional tank stands

## Specifications

Description	
Safe Fill, litres	107,797 (95%)
Length, mm	14'630
Width, mm	2,438
Height, mm	3,635
Total Mass Empty, kg	20,500
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	AS1940, AS1692, UL142

### Self bunded double wall design

- Fluid level dipstick for tank and interstitial space
- Vent pipe for tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Warranty – 5 years structural, 1 year on valves; conditions apply

### Pump bay model standard with:

- Bunded pump bay with lockable weatherproof doors
- Galvanised access ladder and platform; with ladder fitted to either side of the platform (ex-factory)
- Galvanised kick plate and middle rail provided for additional safety of users

*Disclaimer: Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras.*