

# Logitank Blue LTBL 60



## Specifications



Description	
Diesel Safe Fill, litres	55,600
AdBlue®, DEF Safe Fill, litres	7,000
Length, mm	12,192
Width, mm	2,438
Height, mm	2,896
Tare Weight, kg	16,713
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	AS1940, AS1692, UL142, HSNOCOP 24



A self bunded tank for the safe storage and handling of both diesel and AdBlue®, AUS32 or other DEF products from the one unit.

Ideal for refuelling commercial vehicles that use AdBlue®, AUS32 or DEF.



- Self bunded dual compartment design
- Bunded pump bay with lockable weatherproof doors
- Fill and dispense points in the main lockable pump bay
- Galvanised access ladder and platform
- Corner container lock castings for ease of transport
- Access manways
- Warranty – 5 years structural, 1 year on valves; conditions apply

#### Diesel tank standard with:

- Fluid level dipsticks for tank and interstitial space
- Vent pipe for diesel tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm

#### DEF tank standard with:

- Chemical resistant vented tank
- Insulated tank and dispensing line for temperature control
- Stainless steel pipework
- Fluid level dipsticks for tank and interstitial space