



Kommander - LTKO 38



Self bunded double wall design

- Fluid level dipsticks for tank and interstitial space
- UL compliant emergency relief vents on the main tank and interstitial space
- Vent stack with screened rainproof outlet
- Suction foot valve, overfill protection and electronic overfill alarm
- Corner container lock castings for ease of transport
- Access manway
- Warranty* – 5 years structural, 1 year on valves

Options include

- Inspection ladder
- Clip-on pump bay
- Dispensing and fuel management

Specifications

Description

| | |
|----------------------|---|
| Safe Fill, litres | 35,000 |
| Length, mm | 6,058 |
| Width, mm | 2,438 |
| Height, mm | 2,896 |
| Weight (empty) kg | 6,133 |
| Vent Pipe | Standard |
| Fluid Level Dipstick | Standard |
| Compliance | AS1940, AS1692, AS1657, UL142, ULCS601 |

Tank features rounded corners designed to eliminate stress point for improved quality and greater longevity. Also designed for visibility across all external surfaces of the tank.



*Disclaimer: *Terms & Conditions apply. Information and photographs shown are for marketing purposes only. Actual product may vary to images shown due to continual improvement processes, design changes and optional extras*

CONTACT US:

+61 (03) 9775 1366 | sales@fuelco.com.au
FUELCO.COM.AU

Fuelco holds stock of these tanks in ALL states across Australia. For details on availability and pricing, please contact your local state manager.