

Adblue / DEF LTBL 104

A self bunded tank for the safe storage and handling of both diesel and AdBlue®, AUS32 or other DEF products from the one unit.



Tank Specifications

Description	
Diesel Safe Fill, litres	95,628
AdBlue®, DEF Safe Fill, litres	10,000
Length, mm	14,630
Width, mm	2,438
Height, mm	3,635
Vent Pipe	Standard
Fluid Level Dipstick	Standard
Compliance	AS1940, AS1692, UL142, HSW (Haz. Sub.) Reg 2017

Features

- Self bunded dual compartment design
- Bunded pump bay with lockable weatherproof doors
- Fill and dispense points in the main lockable pump bay
- Galvanised access ladder and platform
- Corner container lock castings for ease of transport
- Access manways
- Warranty 5 years structural, 1 year on valves; conditions apply

Diesel tank standard with:

- Fluid level dipsticks for tank and interstitial space
- Vent pipe for diesel tank and interstitial space
- Overfill protection and electronic overfill alarm

DEF tank standard with:

- Chemical resistant vented tank
- · Internal tank is made of Stainless Steel
- Insulated tank and dispensing line for temperature control
- Stainless steel pipework
- Fluid level dipsticks for tank and interstitial space
- Suction foot valve, overfill protection and electronic overfill alarm



Dual Diesel and insulated DEF chemical resistant tanks

GLOBAL CONTACTS

MIDDLE EAST: +971 50 719 7137 | ASIA: +61 430 531 448 | AUSTRALIA: +61 3 9775 1366

SOUTH AMERICA: +56 9 9219 1598 | CENTRAL AMERICA: +50 5 2277 3216