

PIUSI Oil & Fuel Filter Cartridge

FEATURES

- **READY TO USE**
- **REPLACEABLE CARTRIDGE**
- **HIGH EFFICIENCY**
- **SMALL SIZE**

The line filters with spin on cartridges are suitable to be used on both the suction and delivery side of lubricating systems. They are available in 3/4" and 1" inch fittings.

PERFORMANCE

UP TO 100 L/MIN	MAX 3,5 BAR
FLOW RATE	OPERATING PRESSURE
FILTERING CAPACITY 200β/10μ	FILTERING CAPACITY 2β/5-10μ
BIOFUEL	FUEL



60 L/MIN FILTER

100 L/MIN FILTER

PACKAGING

CODE	WEIGHT	DIMENSIONS MM	PACKAGING	
	KG		CARTRIDGE PSC / BOX	FILTER HEAD PCS/BOX
FILTER FOR FUEL AND OIL				
FO77200A	1	200X120X140	1	1
FO9149020	2,6	390X285X140	1	1
FILTER FOR FUEL AND OIL				
FO9359010	-	-	1	-
F16483010	9,2	500X300X200	15	-
FILTER FOR FUEL AND OIL				
F14528000	-	-	-	1


PIUSI Oil & Fuel Filter Cartridge

DIMENSIONS

A B C D F
(MM) (MM) (MM) (MM)

OIL FILTERS

FO777200A	-	100	160	98	-
FO914900A	-	171	236	132	-
FO9149020	-	171	236	132	-
FO0611000	145	-	-	98	3/4" BSP
FO9359000	180	-	-	132	1"1/4 BSP
FO9359010	180	-	-	132	1"1/4 BSP
F16483010	139	-	-	93	-
F14528000	-	100	-	-	3/4" BSP
F15743000	-	171	-	-	1"1/2-16 UNF 1"1/4 BSP



OIL FILTERS

IN THE BOX

- FILTER CARTRIDGE
- INSTRUCTION MANUAL

DETAILS



MATERIALS

- FILTER HEAD: CASTING ALUMINIUM
- CARTRIDGE: SAP/PET
- SEAL: VULCANIZED RUBBER

TECHNICAL DATA

CODE	DESCRIPTION	FLUIDS TYPE	FLOW RATE		INLET / OUTLET BSP	WATER ABSORBING	EFFICIENCY β	MICRO μ m	WORKING PRESSURE BAR
			L/MIN	GPM					
OIL FILTERS									
FO777200A	60 L/MIN FILTER WITH HEAD	B D G O	60	15,9	1"	NO	2	10	12
FO9149020	100 L/MIN FILTER WITH HEAD	B D G O	100	26,4	1"	NO	2	5	12
OIL FILTER CARTRIDGE									
FO9359010	CARTRIDGE 100 L/MIN	B D G O	100	26,4	-	NO	2	5	12
F16483010	KIT CARTRIDGE 60 L/MIN 15 (PCS)	B D G O	60	15,9	-	NO	2	10	12
FILTER HEAD									
F14528000	FILTER HEAD 3/4 BSP 60 L/MIN	-	-	-	1"	NO	-	-	-